



EUROLINK TRACK 230 V

Electrified track in extruded aluminium.

Main voltage 230/250 V. Electrical wiring is located in an extruded PVC insulated housing.

Conductor cross section is 4 mm², for a current rating of 16 A corresponding to a 11.040 W (3x3.680 W) in a 3-phase scheme.

The track is supplied with a series of accessories which will successfully resolve all types of lighting installation requirements.

CE NEMKO
C.C.A. APPROVED



1000 mm. **EL-001**

2000 mm. **EL-020**

3000 mm. **EL-030**



EL-010 DEAD-END

WHITE
BLACK
SILVER



EL-008 FLEXIBLE JOINT

WHITE
BLACK
SILVER



EL-003 LIVE END LX=LEFT
DX=RIGHT

WHITE
BLACK
SILVER



EL-002 EUROLINK ACCESSORIES
UNIVERSAL ADAPTER

WHITE
BLACK
SILVER



EUROLINK TRACK 230 V



EL-007 MEAN CONNECTOR

WHITE
BLACK
SILVER



EL-016 STRAIGHT REINFORCEMENT



EL-004 90° JUNCTION

WHITE
BLACK
SILVER



EL-013 MECHANICAL ADAPTER

WHITE
BLACK
SILVER



EL-011 T JUNCTION

WHITE
BLACK
SILVER



EL-005 LINEAR JOINT

EL-006 (WITHOUT ELECTRIC CONTACT)

WHITE
BLACK
SILVER



EL-012 X JUNCTION

WHITE
BLACK
SILVER



EL-009 WIRE SUSPENSION KIT
ONLY BLACK