


## Foliové kondenzátory Y2, 250VAC .. 300VAC, 10%, RM 10-22,5

## Technické parametry

Tolerance	±20%
Pracovní napětí	250VAC...300VAC
Teplotní rozsah	-40°C...+110°C




Obj.č.	TYP	B [mm]	H [mm]	L [mm]	Min.ks	Cena	Popis
1522094	CFY1.0NF41	4,0	9,0	13,0	50	3,07	1,0nF / 300V / RM10
1510931	CFY2.2NF41	4,0	9,0	13,0	50	3,62	2,2nF / 250V / RM10
1510932	CFY3.3NF41	5,0	11,0	13,0	50	4,12	3,3nF / 250V / RM10
1510933	CFY4.7NF41	5,0	11,0	13,0	50	4,75	4,7nF / 250V / RM10
1510934	CFY10NF41	5,0	11,0	18,0	50	3,80	10nF / 250V / RM15
1522095	CFY100NF41	10,0	18,5	26,5	25	9,62	100nF / 300V / RM22,5

## Kondenzátory foliové WIMA X2, 275V, 20%, RM 15-27,5

## Technické parametry

Jmenovité napětí	275VAC
Tolerance	+/-20%
Rozsah pracovních teplot	-40...+110°C




Obj.č.	Typ	Min.ks	Cena	Popis
1528697	MP3X2N010M275-15	50	8,50	MKP kap. 10nF 275V RM15
1528698	MP3X2N033M275-15	50	9,50	MKP kap. 33nF 275V RM15
1528699	MP3X2N047M275-15	50	10,75	MKP kap. 47nF 275V RM15
1528700	MP3X2N100M275-15	50	15,94	MKP kap. 100nF 275V RM15
1528701	MP3X2N220M275-22	10	27,56	MKP kap. 220nF 275V RM22,5
1528702	MP3X2N330M275-22	10	36,64	MKP kap. 330nF 275V RM22,5
1528703	MP3X2N470M275-27	10	43,03	MKP kap. 470nF 275V RM27,5

## Kondenzátory foliové WIMA Y2, 300VAC, 10%, RM 10-15

## Technické parametry

Jmenovité napětí	300VAC
Tolerance	+/-10%
Rozsah pracovních teplot	-55...+105°C



Obj.č.	Typ	Min.ks	Cena	Popis
1528704	MKPY2N1,0K300-10	50	3,90	MKP kap. 1nF 300V RM10
1528705	MKPY2N1,5K300-10	50	3,90	MKP kap. 1,5nF 300V RM10
1528706	MKPY2N2,2K300-10	50	3,90	MKP kap. 2,2nF 300V RM10
1528707	MKPY2N3,3K300-10	50	4,12	MKP kap. 3,3nF 300V RM10
1528708	MKPY2N4,7K300-10	50	4,37	MKP kap. 4,7nF 300V RM10
1528709	MKPY2N6,8K300-10	50	4,67	MKP kap. 6,8nF 300V RM10
1528710	MKPY2N010K300-15	50	4,67	MKP kap. 10nF 300V RM15
1528711	MKPY2N015K300-15	50	5,50	MKP kap. 15nF 300V RM15
1528712	MKPY2N022K300-15	50	6,92	MKP kap. 22nF 300V RM15




## Kondenzátory fóliové SMD

## Kondenzátory foliové MKT, 50-100V, 5-10%, SMD

## Technické parametry

Jmenovité napětí	63 až 100VDC
Testovací napětí	1,4xUN
Tolerance	10%
Tolerance LDE100NF-63	5%
Rozsah pracovních teplot	-55...+125°C



Obj.č.	Typ	Min.ks	Cena	Popis
1512162	LDE001UF-63	100	14,54	SMD-MKT kap. 1uF 10% 63V 2824
1514124	LDE002,2UF-100	25	11,05	SMD-MKT kap. 2,2uF 10% 100V 5040
1512168	LDE100NF-100	100	6,72	SMD-MKT kap. 100nF 10% 100V 1812
1522078	LDE100NF-63	100	6,50	SMD-MKT kap. 100nF 5% 63V 1210
1512169	LDE220NF-63	100	7,40	SMD-MKT kap. 220nF 10% 63V 1812
1512170	LDE330NF-63	100	7,52	SMD-MKT kap. 330nF 10% 63V 2220