Vishay Draloric



Axial Vitreous Wirewound Resistors



FEATURES

- Complete welded construction
- Vitreous coating
- Enhanced humidity protection
- TCR 100. . .180 ppm/K
- Pure tin plating provides compatibility with lead (Pb)-free and lead containing soldering processes
- Compatible with "Restriction of the use of Hazardous Substances" (RoHS) directive 2002/95/EC (issue 2004)

STANDARD ELECTRICAL SPECIFICATIONS						
GLOBAL MODEL	HISTORICAL MODEL	APPROVED	POWER RATING P _{40 °C} W	RESISTANCE RANGE E12/E24		
		CECC 40201-801		TOL. ±%	Ω	VOLIAGE
G220414	G202	FDG	4	10 5 2 1	R10 - 10K R10 - 10K R36 - 10K ⁽¹⁾ on request	200
G240719	G204	FDK	7	10 5 2 1	R10 - 39K R10 - 39K R10 - 39K on request	350
G260933	G206	FDP	13	10 5 2 1	R15 - 68K R15 - 68K R15 - 68K on request	500
G270947	G207		17	10 5 2 1	R20 - 120K R20 - 120K R20 - 120K on request	650

Note

(1) R10 - R36 on request





Vishay Draloric

PACKAGING TABLE				
SAP	DRALORIC LEGACY	DESCRIPTION	ТҮРЕ	
2C	AC G53	Ammo pack tape 53 mm, 500 pieces	G202	
4B	AB G73	Ammo pack tape 73 mm, 250 pieces	G204	
4C	AC G73	Ammo pack tape 73 mm, 500 pieces	G202	
7B	AB G88	Ammo pack tape 88 mm, 250 pieces	G204	
8B	AB G88 CL	Ammo pack tape 88 mm, CL, 250 pieces	G204	
D1	R1 G53	Reel pack tape 53 mm, 1000 pieces	G202	
F1	R1 G73	Reel pack tape 73 mm, 1000 pieces	G202	
FC	RC G73	Reel pack tape 73 mm, 500 pieces	G204	
IC	RC G88	Reel pack tape 88 mm, 500 pieces	G204	
LA	LA	loose pack, 100 pcs	G206, G207	
LD	-	loose pack, 50 pieces	G204	
LJ	-	loose pack, 200 pieces	G204	
LL	-	loose pack, 400 pieces	-	

DIMENSIONS



For packaging dimensions see separate packaging dimensions page.

	DIMENSIONS in millimeters [inches]					
MODEL	A _{max.}	B _{max.} ⁽¹⁾	C (2)	D _{min.}	Weight (g)	
G 202	13 [0.512]	5.7 [0.224]	0.8 [0.031]	53 ± 1 [2.087 ± 0.039]	1	
G 204	19.3 [0.760]	8.5 [0.335]	0.8 [0.031]	73 ± 1 [2.874 ± 0.039]	2.2	
G 206	32.3 [1.272]	9.8 [0.386]	0.8 [0.031]	107 ± 2 [4.213 ± 0.079]	6.5	
G 207	49.3 [1.941]	10.5 [0.413]	0.8 [0.031]	120 ± 2 [4.724 ± 0.079]	10	

Note

 $^{(1)}$ The body diameter should be increased by 1 mm [0.039"] for ohmic values \leq 10 Ω

(2) C according to IEC60301

Vishay Draloric

Axial Vitreous Wirewound Resistors











Axial Vitreous Wirewound Resistors

Vishay Draloric

PERFORMANCE		
TEST	TEST RESULTS	
Damp Heat, Steady State	$\pm 5 \% \Delta R$	
Climatic Sequence	$\pm 5 \% \Delta R$	
Load Life	± 5 % Δ <i>R</i>	
Short Time Overload	± 1 % Δ <i>R</i>	
Vibration	± 1 % Δ <i>R</i>	
Shock	± 1 % Δ <i>R</i>	
Resistance to Soldering Heat	± 1 % Δ <i>R</i>	



Vishay

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.